



Material Safety Data Sheet

Battery Cleaner & Leak Detector

MSDS ID: 885

*** Section 1 - Chemical Product and Company Identification ***

Part Number: 885

Product Use: Cleans vehicle battery; detects leaks

Manufacturer Information

BG Products Inc.
701 S. Wichita Street
Wichita, KS 67213

Phone: (316) 265-2686
Fax: (316) 265-0718
Emergency # 1-800-424-9300 (CHEMTREC)

*** Section 2 - Hazards Identification ***

Emergency Overview

WARNING

- FLAMMABLE. Do not use or store near flames, sparks, or hot surfaces.
- This product may be harmful by inhalation. Avoid prolonged breathing of fumes. Use with adequate ventilation.
- This product may cause irritation to the eyes and skin. Avoid contact with eyes, skin, and clothing.
- This product may be harmful if it is swallowed.

HMIS Ratings: Health: 1 Fire: 2 Physical Hazard: 0 Pers. Prot.: B

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
2807-30-9	ETHYLENE GLYCOL MONOPROPYL ETHER	1-5
67-63-0	ISOPROPANOL	.5-1.5

Component Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is considered a controlled product under the Canadian Controlled Products Regulations (CPR).

*** Section 4 - First Aid Measures ***

First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact flush with large amounts of water while removing contaminated clothing. If irritation persists, get medical attention.

First Aid: Ingestion

If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel.

First Aid: Inhalation

Move person to non-contaminated air. Give artificial respiration if not breathing. Call a physician if symptoms develop or persist.



Material Safety Data Sheet

Battery Cleaner & Leak Detector

MSDS ID: 885

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.
Keep away from heat, sparks, or open flame.

Hazardous Combustion Products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Extinguishing Media

Dry chemical, foam, carbon dioxide.

Fire Fighting Equipment/Instructions

Fire fighters should wear full-face, self contained breathing apparatus and impervious protective clothing.
Fire fighters should avoid inhaling any combustion products.

NFPA Ratings: Health: 1 Fire: 2 Reactivity: 0 Other: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Contain the discharged material. Remove sources of ignition.

Clean-Up Procedures

Wear appropriate protective equipment and clothing during clean-up. Absorb spill with inert material.
Shovel material into appropriate container for disposal.

Evacuation Procedures

Isolate area. Keep unnecessary personnel away. In case of large spills, follow all facility emergency response procedures.

Special Procedures

Wear appropriate personal protective equipment.

*** Section 7 - Handling and Storage ***

Handling Procedures

Avoid getting this material into contact with your skin and eyes. Wash thoroughly after handling. Use this product with adequate ventilation. Keep container closed.

Storage Procedures

Do not store this material in open or unlabeled containers. Store this product in air-tight containers away from sources of heat and light.

*** Section 8 - Exposure Controls / Personal Protection ***

A: Component Exposure Limits

ISOPROPANOL (67-63-0)

ACGIH: 200 ppm TWA
400 ppm STEL
OSHA: 400 ppm TWA; 980 mg/m³ TWA
500 ppm STEL; 1225 mg/m³ STEL
NIOSH: 400 ppm TWA; 980 mg/m³ TWA



Material Safety Data Sheet

Battery Cleaner & Leak Detector

MSDS ID: 885

500 ppm STEL; 1225 mg/m3 STEL

B: Canadian Provincial Exposure Limits

ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9)

Ontario: 25 ppm TWAEV; 110 mg/m3 TWAEV
Absorption through skin, eyes, or mucous membranes

ISOPROPANOL (67-63-0)

Alberta: 400 ppm TWA; 983 mg/m3 TWA
500 ppm STEL; 1230 mg/m3 STEL

British Columbia: 200 ppm TWA
400 ppm STEL

Manitoba: 400 ppm TWA; 980 mg/m3 TWA
500 ppm STEL; 1225 mg/m3 STEL

New Brunswick: 400 ppm TWA; 983 mg/m3 TWA
500 ppm STEL; 1230 mg/m3 STEL

NW Territories: 400 ppm TWA; 983 mg/m3 TWA
500 ppm STEL; 1228 mg/m3 STEL
Skin notation

Nova Scotia: 200 ppm TWA
400 ppm STEL

Nunavut: 400 ppm TWA; 983 mg/m3 TWA
500 ppm STEL; 1228 mg/m3 STEL
Skin notation

Ontario: 200 ppm TWAEV
400 ppm STEV

Quebec: 500 ppm STEV; 1230 mg/m3 STEV
400 ppm TWAEV; 985 mg/m3 TWAEV

Saskatchewan: 983 mg/m3 TWA; 400 ppm TWA
1230 mg/m3 STEL; 500 ppm STEL

Yukon: 400 ppm TWA; 980 mg/m3 TWA
500 ppm STEL; 1225 mg/m3 STEL
Skin notation

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses; chemical goggles (if splashing is possible).

Personal Protective Equipment: Skin

Use appropriate hand protection.

Personal Protective Equipment: Respiratory

Use NIOSH approved respirator with cartridge, air line, or SCBA as appropriate based on workplace exposure evaluations.

Personal Protective Equipment: General

Use good industrial hygiene practices in handling this material.

* * * Section 9 - Physical & Chemical Properties * * *

Appearance: Orange
Physical State: Liquid
Flash Point Method: COC

Odor: Mild Ammonia
Flash Point: 39°C (102°F)
Boiling Point: Not Determined



Material Safety Data Sheet

Battery Cleaner & Leak Detector

MSDS ID: 885

Melting Point:	Not Determined	Pour Point:	-2°C (28°F)
Specific Gravity:	0.9944	Bulk Density:	8.290 lbs/gal
Solubility (H2O):	Complete	Vapor Pressure:	Not Determined
Vapor Density:	Heavier Than Air	Auto Ignition:	Not Determined
Lower Flammability Limit:	Not Determined	Upper Flammability Limit:	Not Determined
pH:	Not Determined		

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Keep away from heat, ignition sources and incompatible materials. Avoid strong oxidizing agents.

Incompatibility

This product may react with oxidizing agents. Strong oxidizing agents (peroxides, chlorine, strong acids).

Hazardous Decomposition

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Possibility of Hazardous Reactions

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Dose Effects

A: General Product Information

An LD50 value for this product has not been determined.

B: Component Analysis - LD50/LC50

ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9)

Oral LD50 Rat: 3089 mg/kg; Dermal LD50 Rabbit: 960 µL/kg

ISOPROPANOL (67-63-0)

Inhalation LC50 Rat: 72.6 mg/L/4H; Oral LD50 Rat: 4396 mg/kg; Dermal LD50 Rat: 12800 mg/kg; Dermal LD50 Rabbit: 12800 mg/kg

Carcinogenicity

A: General Product Information

No carcinogenicity data available for this product.

B: Component Carcinogenicity

ISOPROPANOL (67-63-0)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 71 [1999], Supplement 7 [1987], Monograph 15 [1977] (Group 3 (not classifiable))

*** Section 12 - Ecological Information ***

Ecotoxicity

No information available for the product.



Material Safety Data Sheet

Battery Cleaner & Leak Detector

MSDS ID: 885

***** Section 13 - Disposal Considerations *****

Waste Disposal Instructions

Dispose of in accordance with all applicable Federal, State, Provincial, and local regulations.

***** Section 14 - Transportation Information *****

US DOT Information

Shipping Name: Consumer Commodity, ORM-D

IMDG Information

Shipping Name: Flammable Liquid, n.o.s. (contains Ethylene Glycol Monopropyl Ether and Isopropyl Alcohol)

UN #: UN1993 **Hazard Class:** 3 **Packing Group:** III **Flash Point:** 39°C

Required Label(s): Limited Quantity

IATA Information

Shipping Name: Flammable Liquid, n.o.s. (contains Ethylene Glycol Monopropyl Ether and Isopropyl Alcohol)

UN #: UN1993 **Hazard Class:** 3 **Packing Group:** III **Flash Point:** 39°C

Required Label(s): Limited Quantity

***** Section 15 - Regulatory Information *****

US Federal Regulations

Components of this product have been checked against the non-confidential TSCA inventory by CAS Registry Number. Components not identified on this non-confidential inventory are exempt from listing (i.e. as polymers) or are listed on the confidential inventory as declared by the supplier.

A: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

ISOPROPANOL (67-63-0)

SARA 313: 1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)

B: Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
ETHYLENE GLYCOL MONOPROPYL ETHER	2807-30-9	Yes	DSL	EINECS
ISOPROPANOL	67-63-0	Yes	DSL	EINECS

State Regulations

Other state regulations may apply. Check individual state requirements.

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
ISOPROPANOL	67-63-0	Yes	Yes	Yes	Yes	Yes	Yes

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
ISOPROPANOL	67-63-0	1 %



Material Safety Data Sheet

Battery Cleaner & Leak Detector

MSDS ID: 885

* * * Section 16 - Other Information * * *

Other Information

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use. You must notify each person to whom this mixture or trade name product is sold. This statement must not be detached. Any copy or redistribution of the Material Safety Data Sheet shall include this statement.

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; CAS = Chemical Abstract Services; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CFR = Code of Federal Regulations; CPR = Controlled Product Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EEC = European Economic Community; EINECS = European Inventory of Existing Commercial Chemical Substances; ELINCS = European List of Notified Chemical Substances; EPA = Environmental Protection Agency; HMIS = Hazardous Materials Information System; IARC = International Agency for Research on Cancer; IATA = International Air Transport Association; IDL = Ingredient Disclosure List; IMDG = International Maritime Dangerous Goods; LC50 = Lethal Concentration 50%; LD50 = Lethal Dose 50%; NDSL = Non-Domestic Substances List; NFPA = National Fire Protection Agency; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; SARA = Superfund Amendments and Reauthorization Act; SCBA = Self Contained Breathing Apparatus; TSCA = Toxic Substance Control Act; WHMIS = Workplace Hazardous Materials Information System.

Contact: Kolin Anglin, Environmental Coordinator

Contact Phone: 316-265-2686

End of MSDS 885